

X-Sight 5 / 5 LRF Series DAY & NIGHT SMART HD RIFLE SCOPES WITH BUILT-IN LRF	page 4
ThOR 5 / 5 LRF Series	page <b>5</b>
THERMAL SMART HD RIFLE SCOPES WITH BUILT-IN LRF  ThOR 5 XD / 5 XD LRF Series	
EXTREME DEFINITION SMART HD THERMAL RIFLE SCOPES WITH BUILT-IN LRF	page 7
ThOR LTV Series THERMAL RIFLE SCOPES	page 8
X-Sight LTV Series	page <b>9</b>
DAY & NIGHT DIGITÂL RIFLE SCOPES  X-Sight 4K Pro Series	
DAY & NIGHT SMART HD RIFLE SCOPES	page 10
Thor Lt Series THERMAL RIFLE SCOPES	page 11
ThOR 4 Series THERMAL SMART HD RIFLE SCOPES	page <b>12</b>
BinoX 4K 4-16x	page 13
DAY & NIGHT SMART HD BINOCULAR BINOX 4T Series	
THERMAL SMART HD BINOCULARS	page 14
OTS-XLT Series HANDHELD THERMAL MONOCULARS	page <b>15</b>
OTS LT Series	page <b>16</b>
THERMAL MONOCULARS  OTS 4T Series	
THERMAL SMART HD MONOCULARS	page 17
ODIN LT Series THERMAL MONOCULARS	page 18
PVS7 Series	page 19
NIGHT VISION GOGGLES PS31 Series	
NIGHT VISION GOGGLES	page <b>20</b>
PVS14 Series NIGHT VISION MONOCULARS	page <b>21</b>
Auxiliary Ballistic Laser 1000/1500  LASER RANGEFINDERS	page <b>22</b>
IR850 Pro	page <b>23</b>
LONG RANGE INFRA-RED ILLUMINATOR IR850 Supernova	
EXTREME RANGE INFRA-RED ILLUMINATOR	page 23
IR940 Pro Long range infra-red illuminator	page 23
Power Weapon Kit 20,000 mAh BATTERY PACK	page <b>23</b>
Extended Life Battery Kit 10,000 mAh BATTERY PACK	page <b>23</b>
10,000 man BATTERY PACK  X-TRAC 5	
TACTICAL REMOTE ACCESS CONTROL	page 23
Tactical Carry Case Deluxe Binoculars Bag	page <b>23</b> page <b>23</b>
Low profile Quick Detach Heavy Duty Mount	page 24
High profile Quick Detach Heavy Duty Mount	page 24
Quick Detach Mount	page 24
RETAIN ZERO WHEN SWAPPING BETWEEN PLATFORMS  X-Sound	page 24
HEARING PROTECTOR	page <b>∠4</b>

# SMART HD OPTICS

# What are Smart HD Optics?

Smart HD Optics have revolutionized the sporting optics market by blending modern technology from smartphones, digital cameras and military electro-optics. ATN's Smart HD Optic innovations are paving the way forward with day/night scopes to binoculars to thermal scopes – they're the most advanced electro-optics available.

ATN is ushering in the future with our Gen 5 platform powered product line. With remarkable performance and improved visual clarity, we are setting a new high bar within our industry.

Optimized with an array of modern sensors and chipsets, ATN's 5th generation platform has been given a facelift with the incorporation of our new Quad Core processor and upgraded ROM memory.

The ultra-powerful Gen 5 platform gives you faster image processing and 4K+ UHD 240 fps video capture for an improved daytime hunting experience. What's more, the new platform will also allow ATN to be first-to-market with an affordable 1280x1024, 12-micron 60 Hz thermal sensor.

Utilizing a 4K+ UHD (4056x3040) sensor (for day/night systems) and 12-micron thermal sensors (1280x1024, 640x480, 320x240 and 160x120) for our thermal line of products, Gen 5-powered Smart HD devices have never been more capable or user friendly. The new Gen 5 platform takes all of our sighting systems up a notch.

Capture and stream your adventures in stunning clarity and quality, thanks to our smart systems' ultra high-definition recording capabilities. You'll also love enhanced ballistic calculation and Smart-Mil Dot reticle capability, along with custom reticle creation in both digital day/night and thermal systems. Offering many of the same features and functions as before, we've included the same intuitive UI (User Interface) and updated mobile app platform.

Our Gen 5 processor packs a punch, so you can experience incredible imagery and performance. Plus, it's cost-effective—enabling us to provide our customers with top quality Smart HD products at an affordable price.

# **ULTRA HD OPTICS**

Experience ATN's Ultra HD Optics like never before! Our new 4K "True Color" Sensor is capable of capturing crisp clear images at the furthest ranges with increased daytime color resolution (4 million colors). With 24,000 shades of grey, you'll also get incredibly smooth nighttime gradations from darkness to light.

All 5th Gen Optics have been redesigned to meet strict specifications to match our 4K sensor performance. The new Quad Core Processor that drives our core allows for faster response, higher FPS rate, better streaming, and the use of a multitude of new image processing techniques.

The next several pages will help familiarize you with just some of the amazing features the new Smart HD and Ultra HD Optics have to offer.

# THE FUTURE OF OPTICS IS HERE!

\* For more details see www.atncorp.com



AMERICAN TECHNOLOGIES NETWORK CORP. 2400 NW 95 Ave, Doral, FL 33172

> Direct Sales: 305-900-6841 Customer Service: 650-989-5100 TOLL FREE **800-910-2862**

info@atncorp.com www.atncorp.com

The products in this catalog are subject to one or more of the export control laws and regulations of the U.S. Government. Pending the model these products are under the control jurisdiction of either the US Department of State or the US Bureau of Industry and Security US Department of Commerce. Export without proper licensing or consent is strictly prohibited.



# X-SIGHT 5 / 5 LRF SERIES DAY & NIGHT SMART HD RIFLE SCOPES WITH BUILT-IN LRF





#### **KEY FEATURES**

- **ULTRA 4K SENSOR**
- **ONE SHOT ZERO**
- DUAL STREAM VIDEO
- SMOOTH ZOOM
- **E-COMPASS**
- WIFI
- DAY/NIGHT MODE
- 3D GYROSCOPE
- **SECORD VIDEO IN REAL 4K**
- BALLISTIC CALCULATOR
- **©** CUSTOM RETICLES
- RAV IN SLOW MOTION
- PROFILE MANAGER
- ULTRA LOW POWER CONSUMPTION
- COMFORTABLE EYE RELIEF

OI LOII TOXI TOXI									
Item	X-Sight 5 3-15x	X-Sight 5 5-25x	X-Sight 5 LRF 3-15x	X-Sight 5 LRF 5-25x					
Laser Rangefider	N	0	Ye	es					
Sensor	AT	N 4K+ 4056x30	40 30/60/120 F	PS					
Magnification	3-15x	5-25x	3-15x	5-25x					
Field of view	9°	6.3°	9°	6.3°					
Field of view	15.7 m / 100 m	11 m / 100 m	15.7 m / 100 m	11 m / 100 m					
Core		ATN Gen V	Quad Core						
Micro Display		1280	x960						
Eye relief		90 ו	mm						
Video Record Resolution		Up to 4K UHD	30/60/120 fps						
<b>Ballistic Calculator</b>	Yes								
WiFi (Streaming, Gallery, & Controls)	iOS, Android								
3D Gyroscope	Yes								
3D Accelerometer	Yes								
<b>RAV (Recoil Activated Video)</b>	Yes								
Electronic Compass		Ye	es						
Smooth Zoom		Ye	es						
Radar		Ye	es						
Reticles	Multiple Patt	erns & Color O <sub>l</sub>	otions, User Cu	stom reticles					
Reticle Editor		Ye	es						
Microphone		Ye	es						
MicroSD card		4 to 64 Gb	(V30 class)						
USB, type C		Ye	es						
Mount	3	0 mm Standard	Rings (included	d)					
Battery life (Li-ion)		Up to 1	4 hours						
Waterproof rating / IP rating		Weather	resistant						
Operating Temperature	-	20°F to +120°F	/ -28°C to 48°C						
Dimensions		14.2"x2.2"x2.1" 360x56x54 mm		15.2"x3"x2.2" 385x76x56 mm					
Weight	1.87  lb / 0.85  kg	1.87  lb  /  0.85  kg	2.1 lb /0.95 kg	2.1 lb /0.95 kg					
Warranty		2 ye	ears						
*Charifications subject to abance with	Contract Con		•						

<sup>\*</sup>Specifications subject to change without notice.

#### **DESCRIPTION**

ATN is moving Electro-Optics innovation forward once again with our 5th Gen X-Sight 5 Ultra HD 4K+ Smart Day/Night Scope. Featuring an upgraded high-performance sensor, the X-Sight 5 gives you ultra-high definition with 4 million more pixels for accurate tones, vivid colors, and a true-to-life visual sensation.

The X-Sight 5 provides the highest sensor resolution on the market. More than double the competition and 33% more than our X-Sight 4K models. Advanced Ballistic calculator helps make sure you hit your target each and every time.

Experience better day and nighttime visual quality and capability along with ambient temperature compensation. It's a 24 hour visual experience like you've never seen!

#### **OPTIONAL ACCESSORIES**



ATN X-TRAC 5
REMOTE CONTROL



ATN WEAPON BATTERY PACK



ATN IR 940 Ir illuminator



ATN LP QUICK DETACH MOUNT



#### DESCRIPTION

The ThOR 5 is our latest generation of thermal scopes and is a revolutionary leap forward.

More power, memory, the latest sensors and custom chips makes Gen 5 a tour de force.

From eyepiece to lens the ThOR 5 outperforms the competition. High resolution OLED display for blacker blacks and richer colors. Upgraded lenses, improved 12  $\mu$ m technology, enhanced algorithms to provide sharp resolution and image quality. A new Quad Core processor with enhanced sensors give Thor 5 stunning image quality in both night and day. Precision is the name of the game in weapon scopes and what you see through a thermal scope matters.

Mountable on standard 30 mm rings Gen 5 now sports a smaller and smoother profile for optimal design and comfort.

ThOR scopes have always been feature rich but Gen 5 has new features to make anyone feel like a kid again. ATN's exclusive Custom Reticle Builder will let your creative side have a real field day.

For those who must make their shots at any distance – LRF has been built in on the side in the smallest form factor ever. Giving you unprecedented precision at up 1000 yards with the internal Ballistic Calculator.\*

One Shot Zero, Profile Manager, Ballistic calculator, Long Battery Life, Smart Mil-Dot Reticle, RAV (Recoil Activated Video), Dual Stream Video, IOS & Android Aps, Radar (for group coordinated action), and many more Features make Gen 5 ThORs a true marvel of science.

\* For LRF models only.

#### **KEY FEATURES**

- ULTRA SENSITIVE SENSOR
- RECORD HD VIDEO
- DUAL STREAM VIDEO
- SMOOTH ZOOM
- E-COMPASS
- 🛜 WIFI
- COLOR MODE

- COMFORTABLE EYE RELIEF
- CUSTOM RETICLES
- **BALLISTIC CALCULATOR**
- **ONE SHOT ZERO**
- RAV
- PROFILE MANAGER
- ULTRA LOW POWER CONSUMPTION

#### **OPTIONAL ACCESSORIES**



ATN X-TRAC 5
REMOTE CONTROL



**ATN X-SOUND** 



ATN WEAPON BATTERY PACK



ATN LP QUICK DETACH MOUNT

# THOR 5 / 5 LRF SERIES THERMAL SMART HD RIFLE SCOPES WITH BUILT-IN LRF

		ThOR 5 320		1	ThOR 5 LRF 320	)		ThOR	5 640			ThOR 5 LRF 640		
Model	ThOR 5 320 3-12x	ThOR 5 320 4-16x	ThOR 5 320 5-20x	ThOR 5 LRF 320 3-12x	ThOR 5 LRF 320 4-16x	ThOR 5 LRF 320 5-20x	ThOR 5 640 2-16x	ThOR 5 640 3-24x	ThOR 5 640 4-32x	ThOR 5 640 5-40x	ThOR 5 LRF 640 2-16x	ThOR 5 LRF 640 3-24x	ThOR 5 LRF 640 4-32x	ThOR 5 LRF 640 5-40x
Item #	TIWST5319A	TIWST5325A	TIWST5335A	TIWST5319LRF	TIWST5325LRF	TIWST5335LRF	TIWST5625A	TIWST5635A	TIWST5650A	TIWST5675A	TIWST5625LRF	TIWST5635LRF	TIWST5650LRF	TIWST5675LRF
Laser Rangefinder		No			Yes			N	lo			Ye	es	
Sensor			320x240 60	) fps 12 μm						640x480 60	) fps 12 μm			
Magnification	3-12×	4-16×	5-20×	3-12×	4-16×	5-20×	2-16×	3-24×	4-32×	5-40×	2-16×	3-24×	4-32×	5-40×
Field of view, degrees	11.6x8.7	8.8x6.6	6.3x4.7	11.6x8.7	8.8x6.6	6.3x4.7	17.6x13.2	12.6x9.4	8.8x6.6	5.9x4.4	17.6x13.2	12.6x9.4	8.8x6.6	5.9x4.4
Core							ATN Gen V	Quad Core T						
Micro Display							OLED displa	ay 1024x768						
Eye relief							90	mm						
Video Record Resolution							Up to 1280x9	960 @ 60 fps						
<b>Ballistic Calculator</b>							Ye	es						
WiFi (Streaming, Gallery, & Controls)			iOS & Android											
Bluetooth				Yes										
3D Gyroscope				Yes										
3D Accelerometer			Yes											
RAV (Recoil Activated Video)				Yes										
Electronic Compass							Ye	es						
Smooth Zoom							Ye	es						
Radar							Ye	es						
Reticles						Multiple Patt	erns & Color O	ptions, User Cu	stom reticles					
Reticle Editor							Ye	es						
Microphone							Ye	es						
MicroSD card							4 to 6	64 Gb						
USB, type C							Ye	es						
Mount						30	) mm Standard	Rings (include	d)					
Battery life (Li-ion)							10	hrs						
Waterproof rating / IP rating							Weather	resistant						
<b>Human Detection Range</b>	750	960	1400	750	960	1400	1250	1600	2150	3300	1250	1600	2150	3300
<b>Human Recognition Range</b>	335	432	630	335	432	630	560	720	960	1485	560	720	960	1485
Human Identification Range	205	260	378	205	260	378	330	432	570	680	330	432	570	680
Operating Temperature						-	20°F to +120°F	/ -28°C to 48°	С					
Dimensions	12.4"x2	.2"x2.1" 316x56	x54 mm	13.4"x3	3"x2.2" 341x76x	56 mm	12.4"x2	.2"x2.1" 316x56	x54 mm	13"x2.2"x2.1" 330x56x54 mm		13.4"x3"x2.2" 341x75x56 mm		14"x3"x2.2" 355x76x56 mm
Weight		1.93 lb / 0.88 kg			2.1 lb / 0.93 kg			1.93 lb / 0.88 kg		2.5 lb / 1.133 kg		2.1 lb / 0.93 kg		2.7 lb / 1.203 kg
Warranty							3 ye	ears						

<sup>\*</sup>Specifications subject to change without notice

## THOR 5 XD / 5 XD LRF SERIES

EXTREME DEFINITION SMART HD THERMAL RIFLE SCOPES WITH BUILT-IN LRF



#### **DESCRIPTION**

As an innovative industry leader, breakthroughs are what we do. ATN delivers on its promise of cutting-edge thermal scope technology with the new ThOR 5 XD. ATN's Gen 5 Thermal Scope is bound to shake up the Electro-Optics industry with its smaller profile, feature-rich, first-to-market 1280x1024, 60 Hz 12 micron, ultra-sensitive HD thermal sensor.

A new Quad Core processor with enhanced sensors give ThOR 5 stunning image quality in both night and day. Precision is the name of the game in weapon scopes and what you see through a thermal scope matters.

#### **KEY FEATURES**

- XTREME DEFINITION SENSOR
- RECORD HD VIDEO
- DUAL STREAM VIDEO
- SMOOTH ZOOM
- **E-COMPASS**
- WIFI
- ULTRA LOW POWER CONSUMPTION

#### **OPTIONAL ACCESSORIES**







ATN HP QUICK DETACH MOUNT

		00					
Model		ThOR 5 XD			ThOR 5 XD LRF		
Monei	ThOR 5 XD 2-20x	ThOR 5 XD 3-30x	ThOR 5 XD 4-40x	ThOR 5 XD LRF 2-20x	ThOR 5 XD LRF 3-30x	ThOR 5 XD LRF 4-40x	
Item #	TIWST51250A	TIWST51275A	TIWST51210A	TIWST51250LRF	TIWST51275LRF	TIWST51210LRF	
Laser Rangefinder		No			Yes		
Sensor			1280x1024	60 fps 12 µm			
Magnification	2-20×	3-30×	4-40×	2-20×	3-30×	4-40×	
Field of view, degrees	17.6x13.2	11.8x8.8	8.8x6.6	17.6x13.2	11.8x8.8	8.8x6.6	
Core			ATN Gen V	Quad Core T			
Micro Display			OLED displa	ay 1024x768			
Eye relief			90	mm			
Video Record Resolution			Up to 1280x	960 @ 60 fps			
Ballistic Calculator			Υ	es			
WiFi (Streaming, Gallery, & Controls)			i0S & /	Android			
Bluetooth			Υ	es			
3D Gyroscope	Yes						
3D Accelerometer	Yes						
RAV (Recoil Activated Video)	Yes						
Electronic Compass	Yes						
Smooth Zoom			Υ	es			
Radar			Υ	es			
Reticles		Multiple	e Patterns & Color O	ptions, User Custom	reticles		
Reticle Editor			Υ	es			
Microphone			Υ	es			
MicroSD card			4 to	64 Gb			
USB, type C			Υ	es			
Mount			30 mm Standard	Rings (included)			
Battery life (Li-ion)				hrs			
Waterproof rating / IP rating			Weather	resistant			
Human Detection Range	2150	3200	4000	2150	3200	4000	
Human Recognition Range	860	1440	1800	860	1440	1800	
Human Identification Range	480	610	720	480	610	720	
Operating Temperature			-20°F to +120°F	/ -28°C to 48°C			
Dimensions	14.4"x2.9"x2.9" 365x73x73 mm	15.5"x2.9"x2.9" 395x73x73 mm	16.7"x2.9"x2.9" 425x73x73 mm	14.4"x2.9"x2.9" 365x96x73 mm	15.5"x2.9"x2.9" 395x96x73 mm	16.7"x2.9"x2.9" 425x96x73 mm	
Weight		2.5 lb / 1.133 kg			2.7 lb / 1.203 kg		
Warranty	3 years						
*Charifications subject to change	Maria Caraltan						

<sup>\*</sup>Specifications subject to change without notice



#### **KEY FEATURES**

ONE SHOT ZERO

Q STEP ZOOM

RECORD VIDEO

♠ 3D ACCELEROMETER

MULTIPLE RETICLES

USB TYPE C

■ ULTRA LOW POWER CONSUMPTION

S ERGONOMIC DESIGN

LIGHT WEIGHT

## **DESCRIPTION**

Ready to hunt like a pro? Look no further than the ThOR LTV thermal riflescope from ATN. Packed with features and super affordable, the ThOR LTV is one of the lightest and easiest-to-use thermal scopes on the market.

Incorporating video recording capability, the ThOR LTV features the latest in advanced 12-micron thermal sensors, a 60 Hz refresh rate, a long-lasting rechargeable battery, and user-friendly controls. Built for tough conditions, the ThOR LTV is available in multiple lenses and sensor resolutions to fit nearly any budget. Mounting is easy with standard 30 mm rings.

The ThOR LTV system is highly-versatile and can be used with a variety of platforms.


Get accuracy, optimal image quality, and convenience that won't break the bank: equip your favorite weapon with an ATN ThOR LTV and see the difference.

OT EUTTON TONO								
	ThOR L	TV 160	ThOR LTV 320			ThOR LTV 640		
Item #	TIWSTLTV112X	TIWSTLTV119X	TIWSTLTV319X	TIWSTLTV325X	TIWSTLTV335X	TIWSTLTV625X	TIWSTLTV635X	TIWSTLTV650X
Resolution	160x120 j	ox / 12 μm	320	0x240 px / 12	μm	64	40x480 / 12 μι	m
Magnification	3–9x	5–15x	3–9x	4–12x	5–15x	2-6x	3–9x	4–12x
Field of view	8.7°x6.5°	6.2°x4.7°	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	17.6°x13.2°	12.6°x9.4°	8.8°x6.6°
Display Resolution				1280x	720 px			
Eye relief				90 ı	mm			
Video Record Resolution				Up to 128	0×720 px			
3D Accelerometer		Yes						
Color modes		White Hot/ Black Hot						
Reticles		Multiple Patterns						
Micro SD card				4 to 6	64 GB			
USB, type C				Ye	es			
Mount			30 m	m Standard R	ings (not inclu	uded)		
Internal Lithium Ion Battery				9 +	hrs			
IP rating				Weather	resistant			
<b>Human Detection Range</b>	475 y/m	625 y/m	715 y/m	910 y/m	1510 y/m	740 y/m	920 y/m	1670 y/m
<b>Human Recognition Range</b>	240 y/m	315 y/m	305 y/m	455 y/m	680 y/m	375 y/m	485 y/m	700 y/m
Human Identification Range	160 y/m	160 y/m 210 y/m 200 y/m 290 y/m 400 y/m 250 y/m 325 y/m 440 y/m						440 y/m
Dimensions		292x56x55 mm / 11.5" x 2.2" x 2.2"						
Weight				1.4 lb/	650 g			
Warranty				3 ye	ears			
*Chapifications subject to abanga without n								

<sup>\*</sup>Specifications subject to change without notice.

# X-SIGHT LTV SERIES DAY & NIGHT DIGITAL RIFLE SCOPES







\*scope view

#### **KEY FEATURES**

- **ODAY/NIGHT MODE**
- RECORD HD VIDEO
- **MULTIPLE RETICLES**
- **3D GYROSCOPE**
- **SECTION STATES SECTION STATES SECTION SECTIO**

#### **DESCRIPTION**

The latest in ATNs HD Optics. The ATN X-Sight LTV scopes are powered by the new revolutionary ATN Obsidian LT Core that is optimized for low power consumption, in a small and ergonomic form factor. Vivid and crisp clarity during the day. Plus, amazing night time performance, delivered by the new QHD+ sensor. Which ATN customers have come to expect and rely on. We have slimmed down the feature offering in this model. Giving the user a simple no frills experience with a price point that's hard to beat. Record HD Videos, get on target fast with our One Shot Zero, operate all night with a 10+ hour battery life. Mount on any platform with standard 30 mm rings. ATN X-Sight LTV — The digital scope for the masses.

#### **SPECIFICATIONS**

X-Sight LTV 3-9x	X-Sight LTV 5-15x				
DGWSXS309LTV	DGWSXS515LTV				
3-9x	5-15x				
ATN QHD+ M	584 Sensor				
2688 x1944	l @ 60 fps				
ATN Obsidia	an LT Core				
1280x7	20 px				
90 n	nm				
Ye	S				
Ye	S				
Yes					
Ye	S				
Multiple F	Patterns				
1280>	720				
4 Gb to	64 Gb				
Chargin	g Port				
30 mm Standard	Rings (included)				
Inclu	ded				
≈ 10	hrs				
Internal Lithium Ion Battery					
Weather resistant					
12.2"x2.2"x2.2"/310x55x55 mm					
1.6 lb / 745 g	1.7 lb / 780 g				
2 ye	ars				
	DGWSXS309LTV 3-9x  ATN QHD+ M 2688 x1944 ATN Obsidia 1280x7 90 n Ye Ye Ye Ye Additional 1280x7 90 n Ye 1280x7 90 n Ye 1280x7 90 n Ye Ye Ye Ye Additional 1280x7 1280x7 90 n Ye Ye Ye Ye Ye Ye Ye Additional 1280x7 1280x7 100 Internal Lithiur Weather r 12.2"x2.2"x2.2"/310x55x55 mm 1.6 lb / 745 g				

<sup>\*</sup>Specifications subject to change without notice.

#### **OPTIONAL ACCESSORIES**



**ATN X-SOUND** 



ATN IR 850 PRO IR ILLUMINATOR



ATN WEAPON BATTERY PACK



ATN QUICK DETACH MOUNT

# X-SIGHT 4K PRO SERIES DAY & NIGHT SMART HD RIFLE SCOPES





\*scope view

#### **KEY FEATURES**

- HD VIDEO WITH 30/60/120 FPS
- **DESCRIPTION** BALLISTIC CALCULATOR
- RECOIL ACTIVATED VIDEO (RAV)
- SMART RANGEFINDER
- SMART MIL DOT RETICLE
- SHARE ON SOCIAL MEDIA
- ONE SHOT ZERO
- **SECOND ULTRA LOW POWER CONSUMPTION**
- PROFILE MANAGER

#### **DESCRIPTION**

For the best night vision scope, look no further than the X-Sight 4, the flagship night rifle scope in ATN's lineup. Industry-leading features are packed into one rifle scope, setting it far ahead of others in its class. The appearance is familiar, resembling a standard night vision scope, but technologically advanced with an Ultra HD sensor for crisp images in Day and Night modes. Ultra-low power consumption enables users to run the scope for up to 18 hours of continuous use. The X-Sight 4 also features a smart range finder, making it easy to gauge how far a target is.

#### **SPECIFICATIONS**

	X-Sight 4K Pro 3-14x	X-Sight 4K Pro 5-20x		
Item #	DGWSXS3144KP	DGWSXS5204KP		
Magnification	3-14x	5-20x		
Field of view at 1000 yds	460 ft (9°)	240 ft (5°)		
Sensor	ATN 4K M265 Sensor	, 3864 (H) x 2218 (V)		
Core	ATN Obsidian	IV Dual Core		
System Resolution	600 lj	p/mm		
Micro Display	1280×720	HD Display		
Eye relief	90	mm		
Video Record Resolution	1080p @ 30/60/120 fps**			
Ballistic Calculator	Yes			
WiFi (Streaming, Gallery, & Controls)	iOS & Android			
Night Vision Mode	Yes			
Reticles	Multiple Patterns	& Color Options		
Micro SD card	4 to 6	64 GB		
USB, type C	Ye	es		
Mount	30 mm Star	ndard Rings		
IR Illuminator	Inclu	uded		
Battery life (Liion)	18+	hrs		
Battery type	Internal Lithiu	m Ion Battery		
Waterproof rating / IP rating	Weather	resistant		
Dimensions (body only)	13.8"×3"×3" 14.9"×3"×3' 350×76×76 mm 379×76×76 m			
Weight	2.1 lb / 0.94 kg	2.2 lb / 1.01 kg		
Warranty	2 years			

<sup>\*</sup>Specifications subject to change without notice

#### **OPTIONAL ACCESSORIES**



AUXILIARY BALLISTIC LASER Rangefinder Series



**ATN X-Sound** 



ATN IR 850 Pro IR Illuminator




ATN WEAPON BATTERY PACK



ATN QUICK DETACH MOUNT

<sup>\*\*</sup>When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.





#### **KEY FEATURES**

- LIGHT WEIGHT
- S ERGONOMIC DESIGN
- USB TYPE C
- **WULTIPLE RETICLES**
- ULTRA LOW POWER CONSUMPTION

#### **DESCRIPTION**

ATN's ThOR LT is a production series comprised of a lightweight thermal rifle scope design fit for close range action. It's a fairly affordable infrared scope made to ensure even the average rifle enthusiast gets to enjoy ATN's modern hunting technologies. It's produced in both 3-6x and 4-8x working configurations.

The ThOR LT thermal scope has a 10-hour battery life, meaning that it can be used continuously throughout a whole day or a night before recharge is needed. It also provides One Shot Zero functionality with Multiple Reticle Patterns and can be mounted on any available standard 30 mm ring. This particular thermal scope series is part of ATN's growing product base of highly effective night vision and thermal optics, and it's designed for easy and simple use. Anyone with a rough idea of how a thermal rifle scope works can operate the ThOR LT with notable ease.

		ThOR LT 160		ThOR LT 320				
Item #	TIWSTLT136X	TIWSTLT148X	TIWSTLT150X	TIWSTLT319X	TIWSTLT325X	TIWSTLT335X	TIWSTLT350X	
Resolution	160x	120 px 17 µm	60 Hz		320x240 px	12 µm 60 Hz		
Magnification	3-6x	4-8x	5-10x	2-4x	3-6x	4-8x	5-10x	
Field of view	8.1°x6.2°	6.2°x4.7°	4.6°x3.3°	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	4.4°x3.3°	
Display Resolution				1280x720 px				
Eye relief				90 mm				
3D Accelerometer				Yes				
Color modes		White Hot / Black Hot						
Reticles		Multiple Patterns						
USB, type C		Charging						
Mount			30 mm Star	idard Rings (n	ot included)			
Battery life (Li-ion)				10+ hrs				
IP rating			W	eather resista	nt			
<b>Human Detection Range</b>	475 m	625 m	995 m	715 m	910 m	1510 m	1620 m	
<b>Human Recognition Range</b>	240 m	315 m	465 m	305 m	455 m	680 m	710 m	
<b>Human Identification Range</b>	160 m	210 m	285 m	200 m	290 m	400 m	415 m	
Operating Temperature		-20°F to +120°F / -28°C to 48°C						
Dimensions		292x56x55 mm / 11.5" x 2.2" x 2.2"						
Weight				1.4 lb / 650 g				
Warranty				3 years				

<sup>\*</sup>Specifications subject to change without notice



#### **KEY FEATURES**

- BALLISTIC CALCULATOR
- RECOIL ACTIVATED VIDEO (RAV)
- SMART RANGEFINDER
- E-COMPASS
- SMART MIL DOT RETICLE
- < SHARE ON SOCIAL MEDIA
- ONE SHOT ZERO
- **□** ULTRA LOW POWER CONSUMPTION
- = PROFILE MANAGER

#### **DESCRIPTION**

As the flagship thermal rifle scope in ATN's lineup, the ThOR 4 is designed for the professional hunter who wants superior functionality. The thermal scope comes loaded with industry-leading features, setting it far above others in its class. The infrared scope has up to 16 hours of battery life while its 4th generation thermal sensor achieves superior performance and supports dynamic range conditions. A smart range finder allows users to easily gauge distances to their target. The ThOR 4 thermal imaging scope for hunting also comes with video recording, WiFi, and Bluetooth capabilities to make sharing captures of your perfect hunt a breeze.

ThOR 4 384 1.25-5x	ThOR 4 384 2-8x	ThOR 4 384 4.5-18x	ThOR 4 384 7-28x	ThOR 4 640 1-8x	ThOR 4 640 1.5-15x	ThOR 4 640 2.5-25x	ThOR 4 640 4-40x
TIWST4381A	TIWST4382A	TIWST4384A	TIWST4387A	TIWST4641A	TIWST4642A	TIWST4643A	TIWST4644A
	Gen 4 3	84x288			Gen 4 6	40x480	
1.25-5x	2-8x	4.5-18x	7-28x	1-10x	1.5-15x	2.5-25x	4-40x
16°×12.5°	12°×9.5°	6°×4.7°	5°×3.8°	32°×25°	24°×19°	12.5°×9.7°	8.3°×6.2°
			ATN Obsidian	IV Dual Core T			
			1280x720	HD Display			
			90	mm			
			Up to 1280x96	60 @ 30/60 fps			
	iOS & Android						
	Yes						
	Multiple Patterns & Color Options						
			From 4 t	to 64 GB			
			Ye	es			
		3	0 mm Standard	Rings (included	d)		
	18+	hrs			16+	hrs	
			Weather	resistant			
13.1"×3"×3" 332×76×76 mm	13.5"×3"×3" 343×76×76 mm	13.8"×3"×3" 351×76×76 mm	14.8"×3"×3" 375×76×76 mm	13.1"×3"×3" 332×76×76 mm	13.5"×3"×3" 343×76×76 mm	13.8"×3"×3" 351×76×76 mm	14.8"×3"×3" 375×76×76 mm
1.93  lb  /  0.88  kg	2.03  lb  /  0.92  kg	2.2 lb / 1.0 kg	2.35 lb / 1.06 kg	1.93  lb  /  0.88  kg	2.03lb/0.92kg	2.2 lb / 1.0 kg	2.35  lb  /  1.06  kg
	3 years						
750 m	960 m	1800 m	3000 m	830 m	1050 m	1950 m	3300 m
335 m	480 m	720 m	1320 m	350 m	530 m	800 m	1450 m
205 m	300 m	430 m	720 m	225 m	330 m	475 m	800 m
	384 1.25-5x TIWST4381A 1.25-5x 16°×12.5° 13.1″×3″×3″ 332×76×76 mm 1.93 lb / 0.88 kg 750 m 335 m	384 1.25-5x TIWST4381A Gen 4 3 1.25-5x 16°×12.5° 12°×9.5°  18+  13.1″×3″×3″ 332×76×76 mm 1.93 lb / 0.88 kg 2.03 lb / 0.92 kg  750 m 960 m 335 m 480 m 205 m 300 m	384 1.25-5x TIWST4381A TIWST4382A TIWST4384A Gen 4 384x288 1.25-5x 12°x9.5°  13.1"x3"x3" 13.5"x3"x3" 332x76x76 mm 1.93 lb / 0.88 kg 2.03 lb / 0.92 kg 2.2 lb / 1.0 kg 750 m 960 m 1800 m 335 m 480 m 720 m 205 m 300 m 430 m	384 1.25-5x         384 2-8x         384 4.5-18x         384 7-28x           TIWST4381A         TIWST4382A         TIWST4384A         TIWST4387A           Gen 4 384x288         1.25-5x         2-8x         4.5-18x         7-28x           16°x12.5°         12°x9.5°         6°x4.7°         5°x3.8°           ATN Obsidian         1280x720         90 ft           Up to 1280x96         iOS & A           iOS & A         Ye           Multiple Patterns         From 4 ft           Ye         30 mm Standard           18+ hrs         Weather           13.1"x3"x3"         13.5"x3"x3"         13.8"x3"x3"         14.8"x3"x3"           332x76x76mm         343x76x76mm         351x76x76mm         375x76x76mm           193 lb / 0.88 kg         2.03 lb / 0.92 kg         2.2 lb / 1.0 kg         2.35 lb / 1.06 kg           750 m         960 m         1800 m         3000 m           335 m         480 m         720 m         1320 m           205 m         300 m         430 m         720 m	384 1.25-5x         384 2-8x         384 4.5-18x         384 7-28x         640 1-8x           TIWST4381A         TIWST4382A         TIWST4384A         TIWST4387A         TIWST4641A           Gen 4 384x288           1.25-5x         2-8x         4.5-18x         7-28x         1-10x           16°×12.5°         12°×9.5°         6°×4.7°         5°×3.8°         32°×25°           ATN Obsidian IV Dual Core T           1280x720 HD Display           90 mm           Up to 1280x960 @ 30/60 fps           iOS & Android           Yes           Multiple Patterns & Color Option           From 4 to 64 GB           Yes           30 mm Standard Rings (included           18+ hrs           Weather resistant           13.1"×3"×3"         13.5"×3"×3"         13.8"×3"×3"         14.8"×3"×3"         375×76×76 mm         332×76×76 mm           1.93 lb / 0.88 kg         2.03 lb / 0.92 kg         2.2 lb / 1.0 kg         2.35 lb / 1.06 kg         1.93 lb / 0.88 kg           750 m         960 m         1800 m         3000 m         830 m           335 m	384 1.25-5x         384 2-8x         384 4.5-18x         384 7-28x         640 1-8x         640 1.5-15x           TIWST4381A         TIWST4382A         TIWST4384A         TIWST4387A         TIWST4641A         TIWST4642A           6en 4 384x288         Gen 4 6         Gen 4 6         Gen 4 6           1.25-5x         2-8x         4.5-18x         7-28x         1-10x         1.5-15x           16°x12.5°         12°x9.5°         6°x4.7°         5°x3.8°         32°x25°         24°x19°           ATN Obsidian IV Dual Core T           1280x720 HD Display           90 mm           Up to 1280x960 @ 30/60 fps           iOS & Android           Yes           30 mm Standard Rings (included)           18+ hrs         Weather resistant           13.1"x3"x3"         13.5"x3"x3"         14.8"x3"x3"         13.1"x3"x3"         13.5"x3"x3"           332x76x76x76 mm         343x76x76 mm         351x76x76 mm         375x76x76 mm         332x76x76 mm         343x76x76 mm           1.93 lb / 0.88 kg         2.03 lb / 0.92 kg         2.2 lb / 1.0 kg         2.35 lb / 1.06 kg         1.93 lb / 0.88 kg         2.03 lb / 0.92 kg           750 m	Time

<sup>\*</sup>Specifications subject to change without notice

## BINOX 4K 4-16X

#### DAY & NIGHT SMART HD BINOCULAR W/ BUILT-IN LASER RANGEFINDER



#### RECORD HD VIDEO



#### **IMAGE QUALITY**

4K Ultra HD technology, combined with our cutting edge Dual Core Processor, gives you unsurpassed image quality with richer and more vivid color tones. Providing the end user with a visual experience like no other.





\* binocular view

Make capturing your experiences in stunning 1080p a regular part of your ops. No more missed opportunities of gathering intel. ATN expands the boundaries of Full HD video recording with rich colors and sharp details. Just insert an SD card to record the scene without any additional USB cables.

#### LASER RANGEFINDER

The new 4K Sensor was incorporated for better visibility and crisper images, but we didn't stop there. We integrated a Laser Rangefinder, so you now have the ultimate binocular package that has everything you want. Not only do you have the ability to see both day and night at your fingertips, but you now have the ability to range your target with absolute accuracy for dope hold over or know how far you need to trek to your next waypoint.



#### **DUAL STREAM VIDEO**

By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your binoculars at the same time, without lag or loss of performance.



	BinoX 4K 4-16x		
Item #	DGBNBN4KLRF		
Sensor	ATN 4K M265 Sensor 3864 (H) x 2218 (V)		
Magnification	4-16x		
Field of view	220 ft		
Display Resolution	1280x720x2		
Interpupillary adjustment range	60-70 mm		
Eye relief	10-30 mm		
Focus Range	10 ft to infinity		
IR illuminator	Yes		
Laser Rangefinder	Yes		
Video Record Resolution	1080p @ 30/60/120 fps**		
Precision to	± 1 y/m		
Range	5-1000 y/m		
IP rating	Weather Resistant		
Charging	USB, type C		
WiFi (Streaming, Gallery, & Controls)	iOS & Android		
Micro SD Card	4 to 64 GB		
Battery life (Li-ion)	18+ hrs		
Dimensions	9.4" x 5" x 2.6" / 240 x 128 x 67 mm		
Weight	2.5 lb / 1.12 kg		
Warranty	2 years		

<sup>\*</sup>Specifications subject to change without notice

<sup>\*\*</sup>When choosing to use this option, the incorporation of your widgets are absent. Widgets would include reticle, time stamp, and logo that are added during video processing.

## **BINOX 4T SERIES**

#### THERMAL SMART HD BINOCULARS W/ BUILT-IN LASER RANGEFINDER



#### LASER RANGEFINDER

We integrated a Laser Rangefinder, so you now have the ultimate binocular package that has everything you want. Not only do you have the ability to see both day and night at your fingertips, but you now have the ability to range your target with absolute accuracy for dope hold over or know how far you need to trek to your next waypoint.



#### **DUAL STREAM VIDEO**


By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your BinoX 4T at the same time, without lag or loss of performance.



#### **IMAGE QUALITY**

By combining Cutting-Edge thermal technology with our Dual Core Processor, we are able to deliver unsurpassed image quality. Giving the end user a visual experience like no other.





\* binocular view

5. 25 TON TORU								
	BinoX 4T 1.25-5x	BinoX 4T 2-8x	BinoX 4T 4.5-18x	BinoX 4T 1-10x	BinoX 4T 1.5-15x	BinoX 4T 2.5-25x		
Item #	TIBNBX4381L	TIBNBX4382L	TIBNBX4384L	TIBNBX4641L	TIBNBX4642L	TIBNBX4643L		
Sensor		384x288			640x480			
Magnification	1.25-5x	2-8x	4.5-18x	1-10x	1.5-15x	2.5-25x		
Field of view	16°×12.5°	12°×9.5°	6x4.7°	32°×25°	24°×19°	12.5°×9.7°		
Display Resolution			1280x7	20x2 px				
Interpupillary adjustment range			60-70	0 mm				
Eye relief			10-30	0 mm				
Focus Range		10 ft to infinity						
Laser Rangefinder	Yes							
Precision to	± 1 y/m							
Range			5-100	0 y/m				
Video Record Resolution			Up to 1280x96	0p @ 30/60fps				
IP rating			Weather	Resistant				
Charging			USB, f	type C				
WiFi (Streaming, Gallery, & Controls)			i0S & <i>F</i>	Android				
Micro SD Card			4 to 6	64 GB				
Battery life (Li-ion)			15+	hrs				
Human Detection Range	750 m	960 m	1800 m	830 m	1050 m	1950 m		
Human Recognition Range	335 m	480 m	720 m	350 m	530 m	800 m		
Human Identification Range	205 m 300 m 430 m 225 m 330 m 475 m							
Dimensions			9.4" x 5" x 2.6" / 2	240 x 128 x 67 mm				
Weight			2.5 lb /	1.12 kg				
Warranty			3 ye	ears				

<sup>\*</sup>Specifications subject to change without notice

# OTS-XLT SERIES HANDHELD THERMAL MONOCULARS



#### **KEY FEATURES**

- S ERGONOMIC DESIGN
- RANGEFINDER
- RECORD VIDEO
- OCOLOR MODES
- USB TYPE C

#### **DESCRIPTION**

The handheld thermal monocular is a handheld device for observation, highest temperature target tracking, distance measurement. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness. The device is mainly applied to outdoor scenarios such as patrolling, law enforcement, search and rescue, drug enforcement, anti-smuggling, hiking, travel, and hunting, etc.

#### **SMART RANGEFINDER**

The device can detect the distance between the target and the observation position.



#### **SPECIFICATIONS**

160x120 nx /				
100X120 px /	′ 17 μm 50 Hz			
2 – 8×	2.5 – 10×			
8.2×6.2	6.5×4.9			
ATN Obsid	ian Core LT			
720×5	540 px			
IP	67			
USB, type C				
720×576 px				
8 Gb				
White Hot / Black H	lot / Red Hot / Color			
≈10	0 hr			
-4°F to +131°F	/ -20°C to 55°C			
6.85" × 2.63" × 2.08	" / 174 × 67 × 53 mm			
0.81 lb	)/370 g			
670	850			
335	425			
170 210				
2 y	ears			
	$2-8 \times \\ 8.2 \times 6.2$ ATN Obsid $720 \times 5$ IP USB, $720 \times 5$ 8 White Hot / Black H $\approx 10$ $-4 ^{\circ} F$ to $+131 ^{\circ} F$ $6.85 ^{\circ} \times 2.63 ^{\circ} \times 2.08$ $0.81$ lb $670$ $335$ $170$			

<sup>\*</sup>Specifications subject to change without notice

# BLACK HOT / WHITE HOT COLOR MODE









\*scope view

# OTS LT SERIES THERMAL MONOCULARS



#### **SPECIFICATIONS**







\*scope view

SPECIFICATIONS						
	OTS L	T 160		OTS L	T 320	
Item #	TIMNOLT136X	TIMNOLT148X	TIMNOLT319X	TIMNOLT325X	TIMNOLT335X	TIMNOLT350X
Resolution	160x120 px /	17 μm 60 Hz		320x240 px /	12 μm 60 Hz	
Magnification	3-6x	4-8x	2-4x	3-6x	4-8x	6-12x
Field of View	8.1°x6.2°	6.2°x4.7°	11.4°x8.6°	8.8°x6.6°	6.3°x4.7°	4.5°x3°
Display Resolution			1280x	960 px		
Eye relief		25 mm				
Color modes		White Hot / Black Hot				
Internal Lithium Ion Battery	10-	10+hr 9+hr				
USB, type C			Char	ging		
IP rating			Weather	resistant		
Human Detection Range	475 m	625 m	535 m	910 m	1510 m	1700 m
<b>Human Recognition Range</b>	240 m	315 m	380 m	455 m	680 m	700 m
Human Identification Range	160 m 210 m 230 m 290 m 340 m		400 m			
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	7.7" x 3" x 2.6"/ 196x76x66 mm					
Weight	1.2 lb / 560 g					
Warranty		3 Years				

<sup>\*</sup>Specifications subject to change without notice

#### **KEY FEATURES**

- S ERGONOMIC DESIGN
- **ATN OBSIDIAN LT CORE**
- **► LONG LASTING INTERNAL BATTERY**
- USB TYPE C

#### **IMAGE QUALITY**




Using our new Obsidian LT Core and Cutting-Edge sensors for sharp crisp images and extended range.



# OTS 4T SERIES THERMAL SMART HD MONOCULARS





#### **SPECIFICATIONS**

#### **CUTTING EDGE DUAL CORE THERMAL SENSOR**

We've combined the next generation thermal sensor with our dual core processor giving you the best thermal monocular ever!

Join the thermal evolution!

#### **FEATURES**

#### **IMAGE QUALITY**

By combining Cutting-Edge thermal technology with our Dual Core Processor, we are able to deliver unsurpassed image quality. Giving the end user a visual experience like no other.

#### **DUAL STREAM VIDEO**

By incorporating a Dual Core Processor, we are now able to provide a much more enhanced experience. Now, you can Live Stream via WiFi to a mobile device, and record in your scope at the same time. Without lag or loss of performance.

#### **RECORD VIDEO**

This feature gives you the opportunity to capture your experiences on video. Using an SD card allows you to record your adventures without any additional USB cables. Never missing a chance to catch your moment on video.

E-COMPASS

DUAL CORE PROCESSOR

< SHARE ON SOCIAL MEDIA

**SOLUTION** ■ ULTRA LOW POWER CONSUMPTION

			01 2011	OAIION	9			
	OTS 4T 384 1.25 - 5x	OTS 4T 384 2 - 8x	OTS 4T 384 4.5 - 18x	OTS 4T 384 7 - 28x	OTS 4T 640 1 - 10x	OTS 4T 640 1.5 - 15x	OTS 4T 640 2.5 - 25x	OTS 4T 640 4 - 40x
# Item	TIMNO4381A	TIMN04382A	TIMNO4384A	TIMNO4387A	TIMNO4641A	TIMN04642A	TIMNO4643A	TIMNO4644A
Sensor		Gen 4 - 384x288 Gen 4 - 640x480						
Magnification	1.25 - 5x	2 – 8x	4.5 – 18x	7 – 28x	1 – 10x	1.5 – 15x	2.5 – 25x	4 – 40x
Field of view, degrees	16x12.5	12x9.5	6x4.7	5x3.8	32x25	24x19	12.5x9.7	8.3x6.2
Core				ATN Obsidian	IV Dual Core T			
Micro Display				1280x720	HD Display			
Eye relief				25	mm			
Video Record Resolution				Up to 1280x96	60 @ 30/60 fps			
WiFi (Streaming, Gallery, & Controls)				i0S & /	Android			
Bluetooth				Y	es			
3D Gyroscope		Yes						
3D Accelerometer				Y	es			
E-Barometer				Y	es			
Smart Range Finder				Y	es			
Electronic Compass		Yes						
Smooth Zoom		Yes						
Microphone				Y	es			
Micro SD card		From 4 to 64 GB						
Micro USB, type C				Y	es			
Internal Lithium Ion Battery		18+	hrs			16+	hrs	
Waterproof rating / IP rating		Weather resistant						
Dimensions	8.7"x3.1"x3" 220x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	9.3"x3.1"x3" 235x80x75 mm	10.2"x3.1"x3" 260x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	8.7"x3.1"x3" 220x80x75 mm	9.3"x3.1"x3" 235x80x75 mm	10.2"x3.1"x3" 260x80x75 mm
Weight	850 g / 1.87 lb	850 g / 1.87 lb	875 g / 1.93 lb	900 g / 1.98 lb	850 g / 1.87 lb	850 g / 1.87 lb	875 g / 1.93 lb	900 g / 1.98 lb
Warranty				3 ye	ears			
Human Detection Range	750	960	1800	3000	830	1050	1950	3300
Human Recognition Range	335	480	720	1320	350	530	800	1450
Human Identification Range	205	300	430	720	225	330	475	800

<sup>\*</sup>Specifications subject to change without notice

# ODIN LT SERIES THERMAL MONOCULARS







# KEY FEATURES

- ATN OBSIDIAN LT CORE
- USB C PORT IN OPTIONAL RECHARGEABLE BATTERY
- Q STEP ZOOM
- S ERGONOMIC DESIGN
- LIGHT WEIGHT

#### **DESCRIPTION**

The ATN ODIN LT has been completely redesigned from top to bottom. This thermal handheld scanner is lighter and ergonomically designed to be hand held or mounted to a helmet or headgear for observation. Slim and ergonomic, fits perfectly in your hand. Using our new Obsidian LT Core and Cutting-Edge sensors for sharp crisp images and extended range. Now you can use single use CR123A batteries or the optional rechargeable battery in this device.

This is one tool you'll want with you at all times. Recovery efforts will seem effortless, finding game will no longer be frustrating or hard to find. Search and Rescue operations will be quicker and more efficient!

	ODIN LT 320 2-4x	ODIN LT 320 3-6x	ODIN LT 320 4-8x	ODIN LT 640 1-4x	ODIN LT 640 2-8x	ODIN LT 640 3-12x
SKU	TIMNODN319X	TIMNODN325X	TIMNODN335X	TIMNODN619X	TIMNODN625X	TIMNODN635X
Resolution	320x240, 60 fps, 12 μm 640x480, 60 fps, 12 μm			ım		
Magnification	2-4x	3-6x	4-8x	1-4x	2-8x	3-12x
Field of view	11.6°x8.7°	8.8°x6.6°	6.3°x4.7°	23.2°x17.4°	17.6°x13.2°	12.6°x9.4°
Core			ATN Obsidi	ian Core LT		
Display Resolution			1280x	960 px		
Eye relief			25 :	mm		
Color modes			White Hot	/ Black Hot		
Battery type			1 x CR123	BA (Li-ion)		
Battery life (Li-ion)		2.5 Hrs (or Optional Rechargeable Battery with 5 Hrs of runtime)				
Charging	USB, type C port is on the Optional Rechargeable Battery					
IP rating		Weather resistant				
<b>Human Detection Range</b>	535 m	910 m	1510 m	715 m	1250 m	1580 m
<b>Human Recognition Range</b>	380 m	455 m	680 m	445 m	580 m	720 m
<b>Human Identification Range</b>	230 m	290 m	340 m	260 m	320 m	350 m
Operating Temperature	-20°F to +120°F / -28°C to 48°C					
Dimensions	5 16"v2 8"v1 81" / 131v71v/6 mm   5 1 1 1 1 1 5 1 6"v2 8"v1 81" / 131v71v/6 mm   5 1 1 1 1 1 1 1 1 1 1 1 1 1 1			5.71"x2.8"x2.01" 145x71x51 mm		
Weight	285 g 342 g 285 g 342 g					342 g
Warranty	3 years					

<sup>\*</sup>Specifications subject to change without notice



ITEM #	MODEL NAME	TUBE CONFIGURATION
NVGOPVS73I	ATN PVS7-3I	Gen. 3*
NVGOPVS73N	ATN PVS7-3N	Gen. 3*
NVGOPVS73WN	ATN PVS7-3WN	Gen. 3*
NVGOPVS7WPT	ATN PVS7-WPT	Gen. WPT™**
NVGOPVS73	ATN PVS7-3	Gen. 3**
NVGOPVS73HPT-A	ATN PVS7-3HPT-A	Gen. 3**
NVGOPVS73W	ATN PVS7-3W	Gen. 3WPT™**
NVGOPVS73WHPT	ATN PVS7-3WHPT	Gen. 3WHPT**

<sup>\*</sup> Requires Export License

<sup>\*\*</sup> No Export Available

ACCESSORY PACKAGES FOR ATN PVS7			
ACMUHMNTMICH	ATN MICH Helmet Mount Assembly USA		
ACMUHMNTPAGS	ATN PAGST Helmet Mount Assembly USA		
ACMPPVSXL3A	ATN 3x Mil-Spec Magnifier Lens		
ACMPPVSXL5A	ATN 5x Mil-Spec Magnifier Lens		

Total darkness IR system	Yes	
Magnification	1x	
Lens System	F1.2, 27 mm	
FOV	40°	
Range of focus	0.25 yd/m to infinity	
Diopter adjustment	-6 to +2	
Controls	Direct	
Automatic brightness control	Yes	
Bright light cut-off	Yes	
Infrared illuminator	Built-in	
Infrared indicator	Yes	
Low battery indicator	Yes	
Power supply	2 x 1,5V(AA type battery)	
Battery life	60 hours	
<b>Environmental rating</b>	Waterproof	
Operating temperature	-60°F to +120°F / -51°C to +49°C	
Storage temperature	-60°F to +185°F / -51 to +85°C	
Dimensions	6,4" X 3" X 6" / 162 X 76 X 152 mm	
Weight	1.5 lbs /0.68 kg	
Warranty	2 years	

- HANDHELD, HEAD-MOUNTED OR HELMET-MOUNTED
- WATERPROOF
- USE TWO AA TYPE BATTERY
- 1X MAGNIFICATION
- STANDARD MILITARY ISSUE
- COMBAT PROVEN
- ONE-KNOB OPERATION
- BUILT-IN INFRARED ILLUMINATOR

#### **DESCRIPTION**

The ATN PVS7 Night Vision Goggles is a robust, dependable, high-performance Night Vision System.

The ATN PVS7 Night Vision Device is identical to the AN/PVS-7 model and is adopted as a standard issue to U.S. Army ground troops, designed to assist viewing and provide reliable service in the most unfavorable conditions. Full U.S. Mil-Spec body with optical assembly, soft carrying case, demist shield, sacrificial filter for objective lenses, shoulder strap, head-mount assembly with 3 brow pads, lens tissue, neck cord and front lens cap.





# PS31 SERIES NIGHT VISION GOGGLES

- DUAL GOGGLE/BINOCULAR
- HANDS-FREE USE
- COMFORTABLE FLIP-UP HEADGEAR
- LIGHTWEIGHT, COMPACT
- WATERPROOF
- BATTERY PACK (OPTIONAL)

#### **SPECIFICATIONS**

Matte Black, Corrosion

Finish	Resistant Fibre re-enforces polycarbonate body	
Capability	Flip-Up On-Off Side Flip-Up On-Off Built-in IR LED with "IR-on" indicator in FOV Low battery indicator in FOV	
Magnification	1x	
Lens System	F/1.18	
FOV	50°	
Range of Focus	0.25 m to infinity	
Diopter Adjustment	+5 to -5 dpt	
Infrared Illuminator	Yes	
Power Supply	1x CR123	
Battery Life	40 h – standard/ 100 h – with Battery Pack	
Standards	MIL-STD-810	
<b>Environmental Rating</b>	IP65	
Dimensions	115 x 178 x 85 mm	
Weight	560 g (w/o battery)	

#### TUBE ITEM # **MODEL NAME CONFIGURATION** NVGOPS313I ATN PS31-3I Gen. 3\* ATN PS31-3N Gen. 3\* NVGOPS313N NVGOPS313WN ATN PS31-3WN Gen. 3\* Gen. 3\*\* NVGOPS313 ATN PS31-3 NVGOPS313HPT-A ATN PS31-3HPT-A Gen. 3\*\* Gen. 3WHPT\*\* NVGOPS313WHPT ATN PS31-3WHPT

NVGOPS314

ACCESSORY PACKAGES FOR ATN PS31		
ACGOPS31BP	PS31 optional battery pack	

ATN PS31-4

Gen. 4\*\*

#### **DESCRIPTION**

The perfect Mixture!

New technology made compatible with your training. The PS31 is a compact, lightweight dual night vision goggle system. It utilizes two high performance image intensifier tubes to provide extremely clear and crisp images under the darkest conditions. This dual tube design provides increased depth perception and outstanding clarity. A built-in IR lets the user easily read a map and function in a total darkness environment.

The PS31 is versatile and easy to adjust, it has become a standard for operators and tactical units. The new design and enhanced FOV, now 50 deg will give you the tactical advantage in the field, providing enhanced capabilities your team needs.





<sup>\*</sup> Requires Export License

<sup>\*\*</sup> No Export Available

# PVS14 SERIES NIGHT VISION MONOCULARS



ITEM #	MODEL NAME	TUBE Configuration
NVMPPV143I	ATN PVS14-3I	Gen. 3I*
NVMPPV143N	ATN PVS14-3N	Gen. 3N*
NVMPPV143WN	ATN PVS14-3WN	Gen. 3WN*
NVMPPV143	ATN PVS14-3	Gen. 3**
NVMPPV143HPT-A	ATN PVS14-3HPT-A	Gen. 3HPTA**
NVMPPV143WPT	ATN PVS14-3WPT	Gen. 3WPT**
NVMPPV143WHPT	ATN PVS14-3WHPT	Gen. 3WHPT**
NVMPPV144	ATN PVS14-4	Gen. 4**

<sup>\*</sup> Requires Export License

<sup>\*\*</sup> No Export Available

ACCESSORY PACKAGES FOR ATN PVS14			
ACMUHMNTMICH	ATN MICH Helmet Mount Assembly USA		
ACMUHMNTPAGS	ATN PAGST Helmet Mount Assembly USA		
ACMPPVSXL3A	ATN 3x Mil-Spec Magnifier Lens		
ACMPPVSXL5A	ATN 5x Mil-Spec Magnifier Lens		
ACMPPVSXWM01	ATN Weapon Mount (PVS14)		

Total darkness IR system	Yes	
Magnification	1x	
Lens System	F1.2, 27 mm	
Proshield lens coating	Yes	
FOV	40°	
Range of focus	0.25 yd/m to infinity	
Diopter adjustment	-5 to +2	
Controls	Direct	
Automatic brightness control	Yes	
Bright light cut-off	Yes	
Infrared illuminator	Built-in	
Infrared indicator	Yes	
Low battery indicator	Yes	
Power supply	1 x 1,5V (AA type battery)	
Battery life	50 hours	
Environmental rating	Waterproof	
Operating temperature	-60°F to +120°F / -51°C to +49°C	
Storage temperature	-60°F to +185°F / -51 to +85 °C	
Dimensions	4.5" x 2.2" x 2" / 114 x 56 x 50 mm	
Weight	0.75 lbs /0.34 kg	
Warranty	2 years	

- MIL-STD-810
- LIGHTWEIGHT
- 1X MAGNIFICATION
- BRIGHTNESS CONTROL
- BRIGHT LIGHT CUT-OFF
- WATERPROOF
- HANDHELD OR HEAD-MOUNTED AS SINGLE EYE GOGGLE

#### **DESCRIPTION**

ATNs PVS14 (1AA) is a rugged, lightweight and versatile Night Vision Monocular designed for the most demanding of nighttime applications. The ATN PVS14 (1AA) can be handheld, head/helmet-mounted for hands free usage or adapted to cameras/camcorders. Originally designed for the U.S. military, these units are of the highest quality in optics, design and functionality. The ATN PVS14 (1AA) is an outstanding choice for professional night vision applications.





## TURN YOUR ATN SMART SIGHT INTO A PRECISE HUNTING MACHINE!

Simple and Quick to attach, the ABL Smart Rangefinder takes just minutes to install. Once active, your ATN Smart Scope's internal Ballistic Calculator will make Instantaneous POI adjustments to your reticle.

#### MAKE EVERY SHOT COUNT!



#### **SPECIFICATIONS**

	ABL 1000	ABL 1500	
ITEM #	ACMUABL1000	ACMUABL1500	
Precision to	± 1 y	r/m	
Range	5-1000 y/m	5-1500 y/m	
Bluetooth	4.1	l	
Environmental rating	Waterproof		
Pairs with smart HD	Obsidian II or higher		
Smart HD optics compatibility	X-Sight 4K Series, ThOR 4 Series		
Battery life	6 months or 5,000 measurements		
Battery type	1 x CR2 type, 3 V		
Dimensions	4.37" x 3.43" x 2.8" / 111 x 87 x 71 mm		
Weight	0.8 lb / 360 g		
Warranty	2 years		

\*Specifications subject to change without notice

# **IR850 PR0**

#### LONG RANGE INFRA-RED ILLUMINATOR



#### **DESCRIPTION**

ATN IR850 Pro an extremely powerful, long range 850 mW infrared illuminator for hunting and search and rescue use.

## **IR850 SUPERNOVA**

#### EXTREME RANGE INFRA-RED ILLUMINATOR



#### **DESCRIPTION**

ATN IR850 Supernova; an extremely powerful, long range infra-red illuminator with adjustable mount, that is perfect for hunting and search and rescue use.

## **IR940**



#### **DESCRIPTION**

The IR940 IR illuminator provides a more covert experience when you want to stay hidden from your prey. Animals and people are not able to see the red glow when looking at the illuminator, even at the light source.

## POWER WEAPON KIT

20,000 mAh BATTERY PACK



#### **DESCRIPTION**

The ATN Extended Power Kit gives you plenty of juice whenever and wherever you need it. Up to 20 hrs of continuous use. Easy to recharge and can power other devices.

Designed to be used with the ATN line of Smart HD Optics: X-Sight 4K, ThOR 4, X-Sight 5, ThOR 5, ThOR LTV.

# EXTENDED LIFE BATTERY KIT

10,000 mAh BATTERY PACK



#### **DESCRIPTION**

Don't let yourself be stuck without a functioning unit, because you didn't bring extra batteries to power your device. ATN Extended Life Battery kit can support your binoculars or monoculars for up to 15 hrs. You can use your devices longer and save money and the environment in the process. Enjoy your activities all day long — whether scouting, camping, bird watching, or surveillance. You can even power your none ATN devices, which are compatible with a micro USB.

Designed to be used with the ATN line of Smart HD Optics: BinoX 4K and BinoX 4T.

### X-TRAC 5



#### **DESCRIPTION**

Use the X-TRAC 5 to connect to your Gen 5 products and have the ultimate control over your device. Adjust settings and activate functions.

## TACTICAL CARRY CASE



#### **DESCRIPTION**

The ATN Tactical Carry Case is a great addition to protect your investment. These carry cases are made out of high quality material with molle webbing and attachments to connect to your loadout gear or compatible backpack, chest rig or harness. Our tactical bags are perfect for the ATN OTS XLT and OTS LT models. Keep your tactical gear protected while out and about in the field.

## DELUXE BINOCULARS BAG



#### **DESCRIPTION**

The ATN Deluxe Binoculars Bag is a comfortable and ergonomic bag with plenty of storage space for your BinoX 4K/4T and or OTS LT/4T units. Plus have easy access to your device and or needed accessories while in the field. Plenty of pockets and mesh webbing, for cables, batteries, power banks, auxiliary illuminators or cell phone.

## LOW PROFILE QUICK DETACH HEAVY DUTY MOUNT



#### **DESCRIPTION**

The Low Profile Quick Detach Mount (LPQDM) is designed specifically to be used with the X-Sight 5, X-Sight LTV, ThOR LT, ThOR LTV and ThOR 5 640 Series of scopes. The LPQDM allows you to quickly switch your scope between rifles; allowing you to take full advantage of the 6 different profiles you can utilize in your Smart HD scope. Simple to install and use, the quick detach mount provides a way for you to swap weapons easily, all while retaining zero.

## HIGH PROFILE QUICK DETACH HEAVY DUTY MOUNT



#### **DESCRIPTION**

The High Profile Quick Detach Mount (HPQDM) is designed specifically to be used with the X-Sight 4K, ThOR 4 and ThOR 5 640/XD Series of scopes. The HPQDM allows you to quickly switch your scope between rifles; allowing you to take full advantage of the 6 different profiles you can utilize in your Smart HD scope. Simple to install and use, the quick detach mount provides a way for you to swap weapons easily, all while retaining zero.

## QUICK DETACH MOUNT

RETAIN ZERO WHEN SWAPPING BETWEEN PLATFORMS



**DESCRIPTION** 

The ATN Quick Detach Mount is a great addition for your new X-Sight 4K or ThOR 4. Take advantage of the profile manager of your scope, move it from platform to platform and still retain zero.

# X-SOUND HEARING PROTECTOR



#### **DESCRIPTION**

ATN X-Sound reduces harmful loud noise down to safe levels below 82 dB and enhances clarity of surrounding low level sounds such as conversations and announcements.

The ergonomic volume control knob allows for total adjustment of the two built-in omni directional microphones, while built-in wireless capability enables hands-free calling and music enjoyment. Or, connect a playing device via the 3.5 mm audio jack.

# THERMAL COYOTE/BOAR TARGET KIT



#### **DESCRIPTION**

The innovative Coyote and Boar Thermal Targets lets you practice usage of your device. The pasters allow you to reuse the targets and get the most out of the package. Universal Thermal Target to get your scope Zeroed and Ready to go quickly. Coyote or Boar Thermal Target size – 30" x 24".

## THERMAL TARGETS



#### **DESCRIPTION**

The ATN Thermal Targets are a great and easy way to Zero in your Thermal Scope, eliminating the frustration of finding a hot or cold target. It uses special material with an included heat source to give you a thermal signature that is easily picked up by your thermal scope.

